

Aluminium Recoil Spring Bushing (PN 01.100) for

- **CZ Tactical Sports Orange (9x19)**
- ***CZ Tactical Sports (9x19)****

Thank you for choosing a high-quality **TECTAL** product!

The *Aluminium Recoil Spring Bushing* has been 100% engineered and “Made in Austria” to replace the standard plastic sleeve, offering the following benefits:

- ✓ increased wear and temperature resistance
- ✓ easy assembly and disassembly of the gun – considerably reducing the risk of damage to the pistol as may happen with the original plastic bushing due to its imprecise and very tight fit requiring the use of (substitute) tools



Supplied Parts:

- 1 pc. *TECTAL Aluminium Recoil Spring Bushing (PN 01.100)*

The following references to and only supplements the OEM manual.

Especially note all the handling and safety instructions contained therein which apply regardless!



CZ refers to this part in their manual as “No. 72 – Sleeve”.

INSTALLATION

1. **Before maintaining or working on any firearm always ensure that it is unloaded and safe!**

While pointing the firearm in a safe direction remove any magazine from the firearm and ascertain it is unloaded by locking the slide to the rear and visually inspecting the chamber before working on or cleaning it! If loaded follow the proper procedures to unload the firearm safely!



Firearms Safety is your responsibility!

2. For disassembly and reassembly of the pistol follow the CZ instruction manual, chapter „Maintenance Instructions”. At this stage the original plastic bushing („No. 72 – Sleeve“) is replaced by installing the *Aluminium Recoil Spring Bushing*.

It is strongly recommended to lightly coat the bushing and guide rod with a suitable gun oil during initial installation and every subsequent maintenance cycle to minimise friction and wear between bushing, guide rod and recoil spring!



NOTES ON MAINTENANCE AND FUNCTION

- During maintenance it is sufficient to wipe the *Aluminium Recoil Spring Bushing* clean on the outside and especially on the inside where it contacts the guide rod and spring.
Due to the coating it is neither necessary nor recommended to use aggressive solvents or abrasive tools for cleaning.
Before re-installation lightly coat the bushing and the guide rod with gun oil (see p. 2).
- By design the *Aluminium Recoil Spring Bushing* has little to no play when installed to ease mounting and dismounting. A little play may result from the variances in the execution of the bushing bore in individual pistols. This is not a defect of the bushing and has no bearing on the proper function.



The spring element **shall NOT** be removed. Removal will lead to damage to the spring element and the bushing!



The *TECTAL Aluminium Recoil Spring Bushing PN 01.100* is **NOT** compatible with the *TECTAL Tungsten-Hybrid Recoil Spring Guide Rod - PN 01.103* due to differences in diameters!

If used in the basic model **CZ Tactical Sports (9X19)**:



The *Aluminium Recoil Spring Bushing* has been tested with and is recommended for use with metal guide rods only!

**In case of any questions please contact us at
office@tectal.at**

© 2018 TECTAL GmbH

www.tectal.at

A-4431 Haidershofen, Austria

This manual or parts thereof may not be used, reproduced or published without express written permission of TECTAL GmbH.